

MULTISTAR COMBINED VEHICLE TECHNICAL DATA

VEHICLE FIGURES

/ Chassis

/ Drivers crew compartment

/ Working height

/ Rescue cage

Gross vehicle mass Super (S)

GVM > 18,0 t

Magirus Team Cab I+8

30.5 m

RC300 for 3 persons / 300 kg

MAGIRUS TEAM CAB

/ Occupant protection according to ECE-R29/03

/ Automatic pneumatic entry and exit hatches

I Entry and ceiling handrails in yellow

I Crew compartment flooring in aluminium chequered sheet

/ 3-point seatbelts (red) for all seats in crew compartment

/ White LED interior lighting

CONCEPT

/ Worldwide unique combination of telescopic boom lift with rescue cage and tank pumper / rescue vehicle

/ 4 models available:

- MultiStar Fire equipped as tank pumper
- MultiStar Rescue equipped as rescue vehicle
- MultiStar LowLiner equipped as tank pumper, UK version
- MultiStar Industrial equipped for industrial fire brigades and special applications

/ Variable equipment storage system AluFire 3 for optimal customisation to individual customer requirements

Integrated water tank for maximized equipment storage capacity

/ Water tank volume: 1,800 l

/ Magirus CAN-Bus technology, FireCan compatible

/ Magirus HMI control panel for an easy and comprehensible vehicle operation

/ Pump capacity: up to 3,000 l/min at 10 bar

/ Aluminium telescopic boom with operating range from -12 m to +30.5 m

/ Outreach 16.5 m (3 persons)

/ Aerial rescue appliance according to EN 1777 with RC300

/ Space reserves for individual additional firefighting equipment and personal gear

/ Continuous ambient, roof and interior lighting for consistent illumination

OPTIONS

/ Transmission options incl. fully automatic Allison transmission

/ Up to 8 breathing apparatus in crew compartment

/ Fixed entry hatches in crew compartment (Euro III / V)

/ Water tank with increased volumes of up to 1,900 l, custom sizes on request

/ Foam tank for volumes of up to 300 l

/ Pressurized foam proportioning system Magirus CaddiSys for proportioning rates of 0.1-6% or alternative manufacturers on request

/ High-pressure pump up to 400 l/min at 40 bar

/ Pneumatic light mast with halogen, xenon or LED technique

I Further suitable model of the Magirus rescue cage series: RC400 for 3 persons

/ Wide range of additional equipment and options available



RC300 for 3 persons / 300 kg



6-way jacking system



Equipment (exemplary loading)



Telescopic boom with operating range from -12 m bis + 30.5 m

Illustrations may include additional options. We reserve the right to make technical changes or improvements at any time without prior notice. Errors and omissions excepted.

MAGIRUS GmbH • Graf-Arco-Straße 30 • 89079 Ulm • Germany www.magirusgroup.com • magirus@cnhind.com